

FLEET ALUMINUM BRIGHTENER

Fleet Aluminum Brightener is an extra-strength, acid-based, aluminum cleaner and brightener designed for non-polished aluminum tanks and trailers, aluminum wheels and for preparing aluminum for painting. Fleet Aluminum Brightener is effective in removing grease, oils, baked-on carbon and diesel smoke. This formula is low foaming.

BENEFITS

- Cleans and Brightens Aluminum
- Economical Dilution Rates
- Safer than Hydrofluoric Acid products



Dilution Ratio: 1:5 to 1:20, 5 gallons makes 105 gallons

To Apply: DO NOT use on glass, polished aluminum or anodized aluminum. DO NOT use Fleet Aluminum Brightener through the high pressure pump. Use through a downstream injector only to prevent damage to the pump.

Directions: INDUSTRIAL USE ONLY. Read the Safety Data Sheet thoroughly before using this product. For heavy soils, mix with water at a 1:5 dilution rate. For light soils, mix at 1:20 (pH 2.3 at dilution). Rapidly wet surface with diluted Fleet Aluminum Brightener and allow it to stand for a few minutes. Clean entire surface lightly with a pressure washer or brush, then rinse thoroughly with plenty of clean water.

Product Information

Part No.	Size	Gross weight	Dimensions (L x W x H) inches	Ship UPS
8.907-711.0	5 gal	52 lb.	12.5 x 12.5 x 15	No
8.907-712.0	55 gal	560 lb.	23.5 x 23.5 x 35	No

LANDA

6398 N. Karcher Way | Aurora, CO 80019
Tel. (877) 526-3235 | www.landa.com

Safety

HMIS Safety Rating: Health	2
HMIS Safety Rating: Flammability	1
HMIS Safety Rating: Reactivity	0
Personal Protective Equipment	D

OSHA/WHMIS/GHS-Compliant SDS available, listed with Infotrac.
For emergency spills call 1-800-535-5053, International 1-352-323-3500.

Certifications

Kosher Certified for use year round, not including Passover.

Smog & Ozone In accordance with AQMD Rule 102, this product contains 0% photochemically reactive ingredients to contribute to smog or attack the earth's ozone layer.

VOC. This product contains 0.2% California Consumer Products VOC at 1:5 ratio.

Technical Data

Color: Light straw, clear

Scent: Sharp

Foam 1-5: 3 = Medium to 2 = Low

Reaction in Hard Water 1-5: 2 = Fair

pH at Full Strength: Less than 1

pH at Use Dilution (1:128 Ratio): 2.3

LANDA

6398 N. Karcher Way | Aurora, CO 80019
Tel. (877) 526-3235 | www.landa.com