

SUNFIRE®

THE ULTIMATE RADIANT HEATERS



BUILT RUGGED TOUGH
FOR LONG-TERM USE.

ONLY SUNFIRE IS
MADE IN THE USA.



QUIET



CLEAN



SAFE

NO SMELL. NO FUMES.



SPECIFICATIONS	SF80	SF120	SF150
BTU/Hour:	80,000	120,000	High 150,000, Low 130,000
Fuel Types:	Diesel, Kerosene, #2 Fuel Oil	Diesel, Kerosene, #2 Fuel Oil	Diesel, #2 Fuel Oil
Fuel Tank Capacity:	6 Gallons	14 Gallons	19 Gallons
Flow Rate (GPH):	.58 for Diesel .56 for Kerosene	.85 GPH for Diesel .78 GPH for Kerosene	High: 1.10 GPH, Low: .97 GPH
Run Time (Approx.):	10 Hrs.	16 Hrs.	High: 17 Hrs., Low 19 Hrs.
Dimensions:	28"L x 18.1"W x 28.1"H	32"L x 28.5"W x 33.75"H	29"L x 35"W x 41"H
Dry Weight:	80 lbs.	120 lbs.	195 lbs.
Wet Weight (Full Tank):	127 lbs.	210 lbs.	320 lbs.
Electrical:	120V .5A 60HZ 12V Pure Sine Power Inverter (800W Minimum)	120V 1.2A 60HZ 12V Pure Sine Power Inverter (800W Minimum)	120V 2A 60HZ 12V Pure Sine Power Inverter (800W Minimum)

COMMON APPLICATIONS

CONSTRUCTION	AUTO SHOPS	FARMS	GARAGE
SPORTS	EVENTS	JOBSITE	POLE BARN



THERMOSTAT OPTION:

All models can be regulated with any standard mechanical or battery-operated wall thermostat. Thermostat not included.

- Not for indoor household residential use.
- Proper ventilation required.

CALIFORNIA PROP 65

This product can expose you to ceramic fibers, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

H2O Power Equipment
Colorado's Largest Pressure Washer Superstore!
Denver: 303-287-7561
Grand Junction /Western Slope: 970-670-5016
Colorado Springs/Pueblo: 719-434-4779

PN 81011822 REV 1 SEP 23



(855) 251-1649
sunfireheaters.com

