HOT WATER SKID SERIES -H2O POWER EQUIPMENT

The Hot water skid series is equipped with a high-performance pressure washing system driven by a twin-cylinder engine, featuring a fixed thermostat for precision temperature control. The heating of the pressurized water is done effectively with a diesel-fired heating system.

UNIT INCLUDES

- Hose • Nozzles: 15°, 25°, 40° and Soap
- Engine oil 10W-30 Lance
- Spray gun · Downstream injector

LIMITED WARRANTY

ALL UNITS 10yr Frame, 5yr Pump, 3yr Engine

FEATURES

- 1750 RPM slow speed
- V-Twin horizontal engine with key-start (battery not included)
- NEMA 4X electrical enclosure with burner on/off rocker switch and hour meter
- Corrosion resistant stainless steel coil cover
- Isolated pump & engine plate with vibration dampeners
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil




INDUSTRIAL

POWERED by

H-SGH35005GC





PUMPS

General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass head
- Heat-resistant ceramic plunger sleeves
- External unloader with bypass hose

FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

HOSE

3/8" x 50' steel-braided Armor Hose™

ENGINES

ENGINE	DISPLACEMENT	FUEL TANK
CRX⊛680	679cc	External
DIMENSIONS		
All Units	L 42" x W 40" x H 38"	

